



### DESCRIPTION

The CLS is a compact and slim Canopy Light for LED lamps. Available in LED 45W or 70W for comparable performance to HID 175W or 250W. Its rugged die cast aluminum housing and tough polycarbonate lens make it ideal for high abuse, vandalism prone areas. U.L. listed for wet locations.

### APPLICATION

Suited for public areas such as underpasses, parking garages, cold storage rooms, building perimeters, schools, corridors and stairwells.

### CONSTRUCTION

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance. Tough injection molded prismatic polycarbonate lens for extra impact resistance. UV stabilized. Silicone rubber gaskets for long life.

### MOUNTING

Contractor friendly Quick Mount System allows fixture to hang while electrical connections are made. Can also be surface conduit wired through 1/2" threaded hubs or pendant mounted with 3/4" pendant.



### LED DRIVER

Electronic LED driver available in universal voltage 120-277V input, 50/60 Hz. Operating temperature from -13°F (-25°C) to 104°F (40°C).

### LED DATA

Nominal Watts	Delivered Lumens	HID Equal
45	4,150	175W
70	5,928	250W

CRI = 70+

Color Temperature = 5000 K

Input Voltage = 120-277V, 50/60 Hz

## CATALOG NUMBER LOGIC

**CLS-**

### Product Series

CLS = Canopy  
LED  
Small

**LD**

### Lamp Type

LD = LED

**45-**

### System Wattage

(LED) 45, 70

**UV**

### Voltage

UV = Universal Voltage  
120 – 277 V