



### **DESCRIPTION**

The VSMD is a 12" x 12" Vandal Resistant Surface Mounting fixture for up to MP 200W or Induction 80W lamps. It has a deeper lens than the VSM fixture allowing for the higher wattage lamps. Its rugged die cast aluminum housing and tough polycarbonate lens make it ideal for high abuse, vandalism prone areas. U.L. listed for wet locations.

### **APPLICATION**

Suited for public areas such as underpasses, parking garages, cold storage rooms, building perimeters, schools, corridors and stairwells.

The Induction 80W version makes an ideal energy saving and long life alternative to traditional MH 175W or MP 150W canopy lights for parking garage applications.

### **HOUSING**

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

### **BALLAST**

High Power Factor, Constant Wattage Autotransformer ballasts, Multi Tap (120/208/240/277V) ballasts. The minimum starting temperature is -20°F (-30°C) for MP.

### **SOCKET**

Medium base, 4KV pulse rated porcelain socket for HID lamps.

### **REFLECTOR**

Die formed cold rolled steel with a high reflectance white polyester powder coat paint finish.

### **GASKET**

Silicone rubber for long life.

### **LENS**

Tough injection molded polycarbonate for extra impact resistance. UV stabilized. Deeper lens for cooler operation of MP 200W and Induction 80W lamps.

### **CATALOG NUMBER LOGIC**

**VSMD-**

**Product Series**  
VSMD = Vandal Resistant  
Surface Mount  
Medium  
Deep Lens

**ID**

**Lamp Type**  
MP = Metal Halide  
Pulse Start  
ID = Induction

**80-**

**Lamp Wattage**  
(MP) 200  
(ID) 80

**120V-**

**Voltage**  
MT = Multi Tap  
120/208/240/277V  
120V = 120V  
277V = 277V

**L**

**Lamp**  
L = Lamp  
Included