



DESCRIPTION

The WGR is a classic glowing circle luminaire for outdoor use that can be wall mounted or ceiling mounted. Available in energy saving LED 20W or 30W sizes for comparable performance to HID 70W or 100W. U.L. listed for wet locations.

APPLICATION

The WGR is suitable for outdoor usage around residential, commercial or industrial buildings, as an entry light above doorways or as a ceiling/canopy light.

CONSTRUCTION

The housing is made of ABS thermoplastic and has a hinged front cover. Injection molded polycarbonate opal lens for an even diffused look. High grade weatherproof silicon rubber gasket for long life.

LED DRIVER

Electronic LED driver available in universal voltage 120-277V input, 50/60 Hz. Operating temperature from -40°F (-40°C) to 104°F (40°C). Dimmable driver standard.

LED DATA

System Watts	Delivered Lumens	HID Equal
20	1,869	70W
30	2,633	100W

CRI = 80+

Color Temperature = 4000 K

Input Voltage = 120-277V, 50/60 Hz

CATALOG NUMBER LOGIC

WGR-

Product Series
WGR = Wallpack
Glow
Round

LD

Lamp Type
LD = LED

30-

Lamp Wattage
(LED) 20, 30

UV

Voltage
UV = Universal Voltage
120 – 277 V