





With Lens



Without Lens



16W and 28W



35W and 45W

### DESCRIPTION

The WOD is an architectural outdoor wallpack that can be used with or without the included lens. Available in energy saving LED 16, 28, 35 and 45W for comparable performance to HID 50-150W.

U.L. listed for wet locations.

### APPLICATION

The WOD is suitable for everyday security lighting usage around residential, commercial or industrial buildings or as an entry light above doorways. The included photocell (120V only) can provide automatic dusk to dawn operation. Dark Sky compliant when used without the lens.

### CONSTRUCTION

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance. Injection molded polycarbonate lens included. Can be used with or without the lens. High grade weatherproof silicon rubber gasket for long life.

### LED DRIVER

Electronic LED driver available in universal voltage 120-277V input, 50/60 Hz. Operating temperature from -4°F (-20°C) to 104°F (40°C).

### PHOTOCELL

Button type photocell included for 120V input operation. For other input voltages the photocell must be changed.

### LED DATA

System Watts	Delivered Lumens	HID Equal
16	1,000	50W
28	1,850	70W
35	2,300	100W
45	3,350	150W

CRI = 70+

Color Temperature = Cool White 5000 K standard.

Consult factory for optional Warm White 3000K version.

Input Voltage = 120-277V, 50/60 Hz

### CATALOG NUMBER LOGIC

WOD-

**Product Series**  
WOD = Wallpack  
Oval  
Dome

LD

**Lamp Type**  
LD = LED

45-

**Lamp Wattage**  
(LED) 16, 28, 35, 45

UV

**Voltage**  
UV = Universal Voltage  
120 – 277 V

### OPTIONS

3000K – Warm White 3000K color temperature LED's.