



DESCRIPTION

The WPP – Wall pack Perimeter Protector is designed for up to LED 126W lamps, HID 400W lamps or Fluorescent 2 x 42W lamps. Its rugged die cast aluminum housing and borosilicate glass lens give it long lasting performance. U.L. listed for wet locations.

APPLICATION

Ideal for lighting the perimeter area around commercial, industrial and residential buildings where higher mounting heights are available and a large area needs to be lit. Its 7.2" depth gives it a sleeker and slimmer profile than other 400W wall packs on the market.

CONSTRUCTION

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

Die formed, anodized aluminum reflector. Silicon rubber gasket for long life.

Prismatic borosilicate glass lens, impact and heat resistant. The door assembly is secured with a stainless steel chain to ensure easy relamping without lens breakage.

BALLAST / DRIVER

Universal Voltage (120-277V) electronic drivers / ballasts for LED and compact fluorescent. High Power Factor, Constant Wattage Autotransformer ballasts. Multi Tap (120/208/240/277V) or 480V ballasts for HID. Minimum starting temperature is -20°F (-30°C) for MP, -40°F (-40°C) for HPS.

MOUNTING

Knockout pattern provided on back casting for mounting to junction boxes. 1/2" threaded entry hubs provided for surface conduit wiring and through wiring.

LED DATA

LED Watts	System Watts	Delivered Lumens	HID Equal
63	77	6,203	250W
95	117	9,305	350W
126	150	12,406	400W

CRI = 70

Color Temperature = 5700 K

Input Voltage = 120-277V, 50/60 Hz

CATALOG NUMBER LOGIC

WPP-

Product Series
WPP = Wall pack Perimeter Protector

MP

Lamp Type
LD = LED
MP = Metal Halide Pulse Start
HP = High Pressure Sodium
FL = Fluorescent quad tube

400-

Lamp Wattage
(LED) 63, 95, 126
(MP) 150, 200, 250, 320, 350, 400
(HPS) 150, 250, 400
(FL) 226 = 2 x 26W
232 = 2 x 32W
242 = 2 x 42W

MT-

Voltage
MT = Multi Tap
120/208/240/277V
UV = Universal Voltage
120 – 277 V
480V = 480V

L

Lamp
L = Lamp
Included

OPTIONS

WPP-WG – Wire Guard for WPP fixture.

PC-XXX – Button Photocell (XXX = specify voltage).