



DESCRIPTION

The WPR2 is an economical and compact low wattage security light. It comes in energy saving Led 17 or 25W versions. Its integrated photocell allows the unit to turn on automatically at dusk and turn off at dawn. U.L. listed for wet locations.

APPLICATION

Ideal for security lighting around commercial, industrial and residential buildings where lower mounting heights are available. Ideal as an automatically operating security light.

BACK PLATE

The housing's back plate is made of high pressure die cast aluminum. The back plate is designed for mounting over an outlet box. A bottom threaded conduit entry hub is also provided for surface conduit wiring.

HOUSING & LENS

Injection molded polycarbonate housing with molded in prismatic lens that provides a forward throw distribution. UV stabilized.

GASKET

Silicone rubber for long life.

PHOTOCELL

Button type photocell included for 120V input operation. For other input voltages the photocell must be changed.

LED DRIVER

Electronic LED driver available in universal voltage 120-277V input, 50/60 Hz. Operating temperature from -13°F (-25°C) to 104°F (40°C).

LED DATA

Nominal Watts	Delivered Lumens	HID Equal
17	1,684	70W
25	2,126	100W

CRI = 80+

Color Temperature = 5000 K

Input Voltage = 120-277V, 50/60 Hz
120V only when used with photocell.

WPR2-

Product Series
WPR = Wall
Pack
Rectangular
2

LD

Lamp Type
LD = LED

25-

Lamp Wattage
(LD) 17, 25

120V-

Voltage
120V = 120V

PC

Photocell
PC = Photocell